

One Click[®] Water Determination Simple and Secure




One Click[®] User Interface

The large color touchscreen features the simple-to-understand and fast-to-operate One Click user interface. All users have their own homescreen with dedicated shortcut buttons to directly start specific routine tasks.



Solvent Manager

Users are protected against contact with chemicals using the Solvent Manager liquid handling device. It is fully controlled by the titrator and offers solvent exchange with One Click without additional user interaction.



Intelligent Burettes

The titrant is automatically recognized, when the burette is installed on the titrator. Important data such as concentration or lifetime is saved on the RFID chip and directly transferred to the titrator, where it is stored and can be monitored. Using the wrong or an expired titrant is therefore impossible.



Flexible Data Export

METTLER TOLEDO Compact Titrators offer a broad range of options for handling your data. Choose whether to export as CSV, PDF or XML files. Devices such as printers or memory sticks can be connected via the USB port and are automatically recognized.



V10S Compact Volumetric KF Titrator

The V10S Volumetric KF Titrator is ideal for fast and precise water content determination with easy operation. Samples with water content between 100 ppm and 100% are analyzed in single measurements or sample series with statistics.

- Color touchscreen with One Click user interface
- User interface in English, German, French, Spanish, Italian, Chinese, Russian, Polish, Korean and Portuguese
- Intelligent burettes with RFID chip saving all relevant titrant data
- Common USB printers or the USB-P25 compact printer for secure and GLP-compliant paper recording

Functionality Overview		V10S
One Click® Titration	User specific Home Screen with Shortcuts	•
	Shortcuts per user	4
	Solvent Control	-
Hot Plug & Play	Solvent Manager	•
	Burette recognition with titrant, concentration and monitoring data	•
	External Dosing Unit for addition of auxiliary reagents	-
	USB printer DIN-A4/US letter / USB-P25 compact printer	•
	USB memory stick / USB barcode reader	•
Automation	InMotion KF Oven Autosamplers	-
User Management	"Expert – Routine" user groups	•
	Preprogrammed METTLER TOLEDO methods	-
Methods and series	KF standard methods	2
	Max. number of user methods	5
	External extraction/dissolution dedicated method type	-
	Number of method function	10
	Number of samples per series	120
	Autostart: automatic start after sample addition	•
	Drift stop for endpoint recognition (absolute and relative, tmax, delay)	•
	Max. number of calculations/results per method	3
	User defined calculations	-
	Statistics of up to 120 samples including result limits check, outlier test	•
	Extra statistical functions as max. srel and multiple determinations	-
	Recalculation of results	•
	Data in Online Screen: time, water count, potential, stirrer speed, volume, drift	•
	Data in measured value table: time, water count, potential, volume, drift	•
	Curves in Online Screen and printout: E-V, E-t, V-t, drift-t, water count-t	•
Online Help	Context sensitive parameter explanation	•
Data Export	USB, Ethernet, PDF	•
Languages	User interface and printouts in English, German, French, Spanish, Italian, Chinese, Russian, Polish, Korean, Portuguese	•
PC software	LabX® Titration connectivity	-
Homogenizer	TTL	-
	Ethernet (TCP/IP)	1
	COM (serial balance connection)	1
	USB host (printer, memory stick, barcode reader, hub)	2
	Integrated Magnetic Stirrer	1
Communication	Pump / Stirrer	1

Technical Specifications

Polarized sensor input	Measurement range	-2000...+2000 mV
	Resolution / Limits of error	0.1 mV / 2 mV
	Polarization current range	0...24 µA
	Polarization current resolution / Limits of error	0.1 µA / 1 µA
Burette drive	Drive resolution	20 000 steps
	Burette resolution (for 5 mL burette)	0.25 µL
	Limits of error	0.3% of the respective volume
	Resolver	32 pulses / mm stroke
	Resolver resolution	0.0625% of burette volume
Environment	Filling time and discharge time	20 s at 100% filling rate
	Ambient temperature	+5...+40 °C
	Atmospheric humidity	max. 80% at 31 °C
Titration dimensions	Width x depth x height / Weight	210 x 333 x 320 mm / 4.2 kg
	Glass beaker	150 mL
Control and display	Touchscreen	VGA 5.7" color TFT, 640 x 480 pixel
Application (depends on the environment and handling)	Drift measurement	Online, < 5 µg/min
	Measurement range	100 ppm...100%
	Repeatability	0.3% at >10 mg H ₂ O

METTLER TOLEDO Group

Laboratory Division
Local contact: www.mt.com/contact

Subject to technical changes
© 06/2017 METTLER TOLEDO. All rights reserved.
30300308B
Marketing Titration / MarCom Analytical

www.mt.com/titration

For more information



One Click is a Registered Trademark of METTLER TOLEDO in Switzerland, the European Union, Russia and Singapore.
LabX is a Registered Trademark of METTLER TOLEDO in Switzerland, USA, China, Germany and a further 13 countries.